

ThermoForm

Material Safety Data Sheet

DATE PREPARED: MARCH 29, 1994

SECTION I PRODUCT: THERMOFORM WALL CAVITY INSULATION UL NO. R9408

Product Identification: ThermoForm Wall Cavity Insulation manufactured by Applegate Louisiana LLC of Monroe, LA

SECTION II CONTROL MEASURES

Respiratory Protection:	OSHA APPROVED NUISANCE DUST MASK		
Ventilation:	YES	Local Exhaust:	YES
Mechanical:	YES-FOR FASTER CURING/DRYING		
Special:	NONE	Other:	NONE
Protective Gloves:	OPTIONAL	Eye Protection:	OPTIONAL
Other Protective Clothing or Equipment:	NOT NORMALLY REQUIRED		
Work/Hygienic Practices:	NO SPECIFIC REQUIREMENT - USE COMMON SENSE!		

SECTION III HEALTH HAZARD DATA

Route(s) of Entry:			
Inhalation?	YES	Skin?	NO
Ingestion?	YES		
Health Hazards (Acute and Chronic):	NONE KNOWN		
Carcinogen?	NO		
NTP?	NO	ARC Monographs?	NO
OSHA Regulated?	NO		
Signs and Symptoms of Exposure:	NONE KNOWN		
Medical Conditions Generally Aggravated by Exposure:		NONE KNOWN	
Emergency and First Aid Procedures:	(INGESTION) IF LARGE AMOUNT IS CONSUMED, SEEK MEDICAL ATTENTION.		

SECTION IV HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Hazardous Components	OSHA PEL	ACGIH TLV	OTHER LIMITS	RECOMMENDED
Recycled Paper Products	N/A	N/A	N/A	
OSHA particulates not otherwise regulated:				
Total Dust		N/A	15mg/m3	N/A
Respirable Fraction	N/A	5 mg/m3	N/A	
Boric Acid	CAS NO: 10043-35-3	N/A	10mg/m3	N/A
Ammonium Sulfate	CAS NO: 7783-20-2	N/A	15mg/m3	N/A
Dry Adhesive	CAS NO: 9005-25-8	N/A	N/A	N/A
Calcium Sulfate	CAS NO: 00778-18-9	N/A	10mg/m3	OSHA PEL 8 HR 15mg/m3 nuisance

SECTION V PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point:	N/A		
Specific Gravity (H ₂ O = 1):	N/A	Evaporation Rate	
Vapor Pressure (mm Hg.):	N/A	(Butyl Acetate = 1):	N/A
Melting Point:	N/A	Solubility in Water:	None
Vapor Density (AIR = 1):	N/A	Odor:	No Odor
Colors:	Grey		

SECTION VI REACTIVITY DATA

Stability:	Stable	
Incompatibility (Materials to Avoid):	N/A	
Hazardous Decomposition or Byproducts:		Combustion products as typical wood
Hazardous Polymerization:	Will not occur	
Conditions to Avoid:		Prolonged temperatures exceeding 180 degrees Fahrenheit

SECTION VII FIRE AND EXPLOSION HAZARD DATA

Flash Point (Method Used):	N/A	
Extinguishing Media:	Any standard method	
Flammable Limits:	N/A	
LEL:	N/A	
UEL:	N/A	
Unusual Fire and Explosion Hazards:	NONE KNOWN	
Special Fire Fighting Procedures:	No special method; material is treated for flame resistance	

SECTION VIII PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to Be Taken in Case Material is Released or Spilled:	Scoop up large quantities and use or dispose.
Waste Disposal Method:	Dispose of material in accordance with federal and/or state regulations covering solid waste disposal.
Preccautions to Be Taken in Handling and Storing:	Store material in a dry place.
Other Precautions:	None required.

Applegate Louisiana LLC
2500 Jackson Street
Monroe, LA 71202
Phone 800-854-1907 or 318-323-1337 Fax 318-323-1338